


Interchangeable Thread Inserts for TESA Micrometers Series AC

With measuring faces specially designed for checking pitch diameters.



- Hardened steel
- Supplied in sets or pairs
- Fixing rod: 3,5 mm dia., 15,5 mm long

For unified inch threads, UN, UNC, UNF... 60° flank angle

For Whitworth threads, 55° flank angle

For ISO metric threads, flank angle 60°

No	=
00250015	Set of inserts 64 ÷ 2,5 in
<i>COMPOSITION OF THE SETS:</i>	
00250000	AC UN,UNC,UNF 64 ÷ 42 in
00250001	AC UN,UNC,UNF 42 ÷ 25 in
00250002	AC UN,UNC,UNF 25 ÷ 17 in
00250003	AC UN,UNC,UNF 17 ÷ 10 in
00250004	AC UN,UNC,UNF 10 ÷ 6,5 in
00250005	AC UN,UNC,UNF 6,5 ÷ 4 in
00250006	AC UN,UNC,UNF 4 ÷ 2,5 in

No	=
00250115	Set of inserts, whitworth 60 ÷ 3 in
<i>COMPOSITION OF THE SETS:</i>	
00250100	AC whitworth 60 ÷ 48 in
00250101	AC whitworth 48 ÷ 40 in
00250102	AC whitworth 40 ÷ 32 in
00250103	AC whitworth 32 ÷ 24 in
00250104	AC whitworth 24 ÷ 18 in
00250105	AC whitworth 18 ÷ 14 in
00250106	AC whitworth 14 ÷ 10 in
00250107	AC whitworth 10 ÷ 7 in
00250108	AC whitworth 7 ÷ 4,5 in
00250109	AC whitworth 4,5 ÷ 3 in

No	=
00240015	Set of inserts ISO 0,40 ÷ 6,00
<i>COMPOSITION OF THE SETS:</i>	
00240000	ISO 0,4 ÷ 0,50
00240001	ISO 0,5 ÷ 0,60
00240002	ISO 0,6 ÷ 0,80
00240003	ISO 0,8 ÷ 1,00
00240004	ISO 1,0 ÷ ,25
00240005	ISO 1,25 ÷ 1,50
00240006	ISO 1,5 ÷ 2,00
00240007	ISO 2,00 ÷ 2,50
00240008	ISO 2,5 ÷ 3,00
00240009	ISO 3,00 ÷ 4,00
00240010	ISO 4,00 ÷ 5,00
00240011	ISO 5,0 ÷ 6,00

Setting Standards for Screw Thread Micrometers - Metric, 60° or 55° flank angle



- Hardened steel
- Insulating sleeve marked with actual size

60° flank angle, metric

60° flank angle, imperial

55° flank angle, metric

No	A	T
	Flank angle	mm
00240501	60°	25
00240502	60°	50
00240503	60°	75
00240504	60°	100
00240505	60°	125

No	A	T
	Flank angle	in
00250501	60°	1
00250502	60°	2
00250503	60°	3
00250504	60°	4
00250505	60°	5

No	A	T
	Flank angle	mm
00240601	55°	25
00240602	55°	50
00240603	55°	75